

Integrated Telephone System

**KX-TS820** 

New business-use ITS
 10 One Touch Speed Dial Key
 Ringer LED for Incoming call

# Success in Business Begins with Reliable Tools



# **KX-TS820**

### Integrated Telephone System



## Strong Support for All Types of Business

The Integrated Telephone System combines function and design to meet a wide range of business situations. All required functions are designed based on special business specifications and ensure extremely easy operation.

#### **Outstanding Features with Built-In Quality**

New business-use

ITS

#### New businessuse ITS

To reliably support all business activities, the Integrated Telephone System features a wide range of indispensable functions, a comfortable handset and 2-Step Tilt Angle.

#### 10 One Touch Speed Dial Key

10 one-touch speed dial numbers are ideal for storing emergency or frequently dialed numbers. You can also store and retrieve 20 phone numbers for two-touch speed dialing. A total of 30 speed dial numbers will save you searching and dialing time.

#### Ringer LED for Incoming call



You can confirm incoming calls visually. Ringer Indicator flashes to indicate there is an incoming call. Convenient when waiting for a call.

#### 2-Step Tilt Angle

The 2-Step Tilt Angle allows easy adjustment when the telephone is placed on a desk. Careful engineering and design ensure easy use while minimizing user inconvenience.



#### Wall Mountable

30

There's no need to worry if you can't find a suitable place to put your KX-TS820. You can mount it right on the wall for functional use.



#### **Other Features**

- Programmable Flash Time setting
- Long Handset Cord (39 cm)

Dial Lock (4 digits PIN)

Ringer Indication (LED)

Sn	ecit	icat	ions
J P	CCII	icut	10113

Call Restriction	—	Insertable Pause	• (3.5 sec)
One Touch Dial (Stations)	10 stations	Ringer Selector (step)	SW (Off / Low / High)
Redial	<ul> <li>(Last number only)</li> </ul>	Volume	Electrical (4 steps)
One-Touch Tone Switching	•	Wall Mountable	•
Tone/Pulse Setting	Programmable	Dimensions (W x D x H)	172 mm x 220 mm x 93 mm
Timed Flash	600 ms	Weight	426 g

